WINCH MOUNT INSTALLATION INSTRUCTIONS **SUZUKI:** 450 King Quad 07-10 / 500 King Quad 09-17

700 King Quad 05-07 / 750 King Quad 08-19

ITEM	QTY.	PART#	DESCRIPTION
1	1	1554-1	Winch Mount Plate
2	4	HDW2050	5/16 x 3/4 Hex Bolt
3	6	HDW7058	5/16 Nylock Nut
4	4	HDW9002	5/16 Flat Washer
5	2	HDW2056	5/16 x 2 Hex Bolt
6	2	HDW9407	7/8 U-Clamp

NOTE: Fairlead is not included with this winch Mount Kit

Remove the lower front plastic skidpan and upper plastic bumper cover.

Position the winch mount behind the front bumper framework on the inside of the frame tabs. The top front of the winch mount will go in front of the front bumper tubes. Align the four lower holes in the winch mount with the holes in the frame. Install four 5/16" x 3/4" hex bolts through the frame tabs and the winch mount. Secure using four 5/16" flat washers and 5/16" nylock nuts.

Slide a 7/8" u-clamp over each front bumper tube facing inward and align with the upper tabs on the winch mount. Secure with a 5/16" x 2" hex bolt from the outside and a 5/16" nylock nut on the inside. Be careful not to overtighten.

Orientate the winch so the cable pulls off the bottom of the drum and bolt to the plate using the hardware provided with the winch.

